

ADAPTIVE ARRAYS IN PACKET RADIO NETWORKS

FINAL REPORT

R. T. COMPTON, JR.



JULY 1991

U. S. ARMY RESEARCH OFFICE

DAAL03-89-K-0073

THE OHIO STATE UNIVERSITY ELECTROSCIENCE LABORATORY

91-08295

91 8 20 012

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

REPORT DOCUMENTATION PAGE									
1a. REPORT SECURITY CLASSIFICATION				16. RESTRICTIVE MARKINGS					
Unclassified				3. DISTRIBUTION / AVAILABILITY OF REPORT					
2a. SECURITY CLASSIFICATION AUTHORITY									
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE				Approved for public release; distribution unlimited.					
4. PERFORMI	ng organizat	TION REPORT NUMBE	ER(S)	5. MONITORING ORGANIZATION REPORT NUMBER(S)					
			ARO 26274.1-EL						
Ga. NAME OF	PERFORMING	ORGANIZATION	6b. OFFICE SYMBOL	7a. NAME OF MONITORING ORGANIZATION					
The Ohio State University			(If applicable)						
ElectroScience Laboratory				U. S. Army Research Office					
6c. ADDRESS (City, State, and ZIP Code)				7b. ADDRESS (City, State, and ZIP Code)					
1320 Kinnear Road Columbus, Ohio 43212				P. O. Box 12211 Research Triangle Park, NC 27709-2211					
	FUNDING/SPC	INSORING	86. OFFICE SYMBOL	9. PROCUREMEN	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER				
ORGANIZA	-	rch Office	(If applicable)						
	City, State, and		<u> </u>		FUNDING NUMBER		073		
	ox 12211	25 (004)		PROGRAM	PROJECT	TASK		WORK UNIT	
		e Park, NC 2	7709-2211	ELEMENT NO.	NO.	NO.		ACCESSION NO	
11 TITLE (local	turio Comunica (Tamification)			L	<u> </u>		<u> </u>	
	11. TITLE (Include Security Classification) ADAPTIVE ARRAYS IN PACKET RADIO NETWORKS								
AUAr	IIVE AKKA	IS IN PACKET	RADIO NEIWORKS						
12. PERSONAI	L AUTHOR(S)	R.T. Co	omnt on						
13a. TYPE OF	REPORT	13b. TIME C		14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT				OUNT	
		1/89 TO 8/3/90	July 31 1991 5						
16. SUPPLEME	NTARY NOTA	The view,	opinions and/or	findings co	ontained in a	this	report	are those	
of the a	uthor(s)	and should no	t be construed a	s an officia	l Department	of	the Arm	y position,	
17.	COSATI		18. SUBJECT TERMS (Continue on reven	e if necessary and	ident	ify by block	number)	
FIELD	GROUP	SUB-GROUP	Packet Radio Communication	e	Networks				
	 		Communiteacton	.5	Adaptive Arr	ays			
19. ABSTRACT	(Continue on	reverse if necessary	and identify by block i	rumber)					
Research under ARO Contract DAALO3-89-K-0093 is described. This work involved the use of adaptive antennas in packet radio									
networks.									
		LITY OF ABSTRACT		21. ABSTRACT SE	21. ABSTRACT SECURITY CLASSIFICATION				
	SIFIED/UNLIMIT F RESPONSIBLE	ED SAME AS I	RPT. DTIC USERS		classified				
LAG. TANNE U	r near-unaidle	INUIVIOUAL		220. TELEPHONE	Include Area Code)	22c.	OFFICE SYN	JOEN	

UNCLASSIFIED		
RECURITY CLASSIFICATION OF THIS PAGE		
	•	
		j
		<u> </u>
]
		ļ
		ļ
		1
		Į
		1
		İ
		j
		j
		1
		1
		1
		J
		I
		1
		i
		ł

UNCLASSIFIED

FINAL REPORT

- 1. ARO PROPOSAL NUMBER: 26274-EL
- 2. PERIOD COVERED BY REPORT: 1 March 1989 31 August 1990
- 3. TITLE OF PROPOSAL: Packet Radio Networks with Adaptive Arrays
- 4. CONTRACT OR GRANT NUMBER: DAAL03-89-K-0073
- 5. NAME OF INSTITUTION: The Ohio State University
- 6. AUTHOR OF REPORT: R. T. Compton, Jr.
- 7. LIST OF MANUSCRIPTS SUBMITTED OR PUBLISHED UNDER ARO SPONSORSHIP DURING THIS REPORTING PERIOD, INCLUDING JOURNAL REFERENCES:
 - (a) H.-C. Yu and R. L. Hamilton, "Optimal Routing in Packet Radio Networks," submitted to *IEEE Transactions on Information Theory*, May 1989.
 - (b) R. L. Hamilton, "Optimal Routing Based on Limited Information," submitted to IEEE Transactions on Automatic Control, July 1989.
 - (c) R. L. Hamilton and B. S. Leung, "Product Form Solutions for a Tandem Packet-Radio Queueing System," submitted to IEEE Transactions on Automatic Control, January 1990.
 - (d) J. Ward and R. T. Compton, Jr., ":Improving the Performance of a Slotted ALOHA Packet Radio Network with an Adaptive Array," to appear in *IEEE Transactions on Communications*.
 - (e) J. Ward and R. T. Compton, Jr., "High-Throughput Slotted ALOHA Packet Radio Networks with Adaptive Arrays," to appear in *IEEE Transactions on Communications*.
- 8. SCIENTIFIC PERSONNEL SUPPORTED BY THIS PROJECT AND DE-GREES AWARDED DURING THIS REPORTING PERIOD:
 - R. T. Compton, Jr., PI
 - R. L. Hamilton, Jr., PI
 - A. S. Galanopoulis, Graduate Student
 - F. W. Vook, Graduate Student
 - J. Ward, Graduate Student Received Ph.D., August 1990

STATEMENT OF THE PROBLEM

This research considered the use of adaptive antennas in packet radio networks (PRNs). By using an adaptive array at a packet radio terminal, the receiving pattern of a terminal can change in response to each received packet. For example, in a slotted system, a terminal with an adaptive array can receive one or more packets correctly in a slot even when the slot contains colliding packets, because the array automatically nulls the colliding packets.

Under this contract, we have first studied the performance of a single packet radio terminal using a multibeam adaptive array. The throughput-delay performance of the packet terminal has been evaluated for both slotted and unslotted channels. In addition, we have also studied the throughput-delay performance of a small slotted network that uses a single-beam adaptive array at each terminal.

SUMMARY OF THE MOST IMPORTANT RESULTS

Previous work [1] had shown that the performance of a packet radio terminal could be substantially improved by using a single-beam adaptive array at the terminal. The improvement is similar to that of Carrier Sense Multiple Access (CSMA) [2]. However, an adaptive array has the advantage over CSMA that, unlike CSMA, it does not require all terminals in the network to be able to hear one another.

Under this contract, we first studied the throughput-delay performance of a single packet radio receiver that uses a multibeam adaptive array. A multibeam adaptive array is one that forms several beams (or patterns) simultaneously from the same array elements. We have shown that with a multibeam adaptive array, a packet radio terminal can achieve average throughputs of 3 or 4 packets per packet width. This result can be achieved in either slotted or unslotted systems. (The method of acquiring packet timing and adapting the array pattern is, however, different for slotted and unslotted systems.)

Second, under this contract we have also studied what happens when adaptive arrays are used in multihop (PRNs). As part of this work, we have developed some tools needed for predicting the performance of multihop PRNs with adaptive arrays. Specifically, an approximate algorithm has been developed for determining the average packet delay in slotted ALOHA PRNs with adaptive arrays. Comparisons of the

results predicted by this algorithm with those obtained from simulations indicate that this algorithm is accurate for most traffic levels.

Our results for network performance with adaptive arrays show that adaptive arrays dramatically increase the throughput-delay performance of a slotted ALOHA PRN. For example, we have shown that the addition of a simple 3-element adaptive array to each node in a 10-node network dramatically improves the average delay. Moreover, most of the improvement is obtained by using an array with only one null. The improvement does depend, of course, on the network traffic. Performance improvements due to the adaptive arrays occur mainly at medium to high traffic levels. (At low traffic levels, there are so few collisions that adaptive arrays have little effect. But at higher traffic levels, adaptive arrays significantly reduce the frequency of collisions and hence reduce delays.)

- [1] M. Azizoglu, R. T. Compton, Jr., F. D. Garber, G. M. Huffman and H. C. Yu, "Adaptive Arrays in Satellite Packet Radio Communication Systems," Technical Report 718163-2, August 1987, The ElectroScience Laboratory, Department of Electrical Engineering, Ohio State University, Columbus, OH 43212; prepared for the National Aeronautics and Space Administration, Lewis Research Center, 21000 Brook Park Rd., Cleveland, OH 44135 under Contract No. NAS3-24888.
- [2] L. Kleinrock and F. A. Tobagi, "Packet Switching in Radio Channels: Part I Carrier Sense Multiple-Access and Their Throughput-Delay Characteristics," *IEEE Transactions on Communications*, Vol. COM-23, No. 12 (December 1975), pp. 1400-1416.



Acces	sion For	r					
NTIS	GRA&I						
DTIC	TAB						
Unanneumoed							
Justification							
D		· · · · · · · · · · · · · · · · · · ·					
By							
Distribution/							
Availability Codes							
	Avail a	nd/or					
Dist .	Speci	al					
1							
11/ N							
n'							